



Mobil Delvac™ 1 Transmission Fluid 50

Mobil Commercial Vehicle Lube, United States

Supreme Performance Transmission Lubricant

Product Description

Mobil Delvac™ 1 Transmission Fluid 50 is a fully synthetic, manual transmission lubricant engineered to meet the most demanding extended drain and OEM warranty requirements. It is recommended for year-round lubrication of manual transmissions in light to severe duty on- and off-highway equipment operating in a wide range of environments. Designed to provide maximum protection and extended operating life to heavy duty transmissions, Mobil Delvac 1 Transmission Fluid 50 provides significant advantages over conventional sulphur-phosphorus gear oils, including outstanding high-temperature performance, oxidation stability, wear protection, and corrosion control.

It has the same viscosity as most SAE 50 engine oils and SAE 90 gear lubricants at the high end of the temperature-viscosity scale, and because of its inherently high viscosity index, it provides stronger film strength at higher temperatures than conventional oils. Mobil Delvac 1 Transmission Fluid 50 also ensures effective lubrication at below freezing temperatures without channelling.

Outstanding performance is confirmed by approval against the Mack TO-A Plus 500,000 mile extended service classification for Mack T300 series manual transmissions. Mobil Delvac 1 Transmission Fluid 50 meets or exceeds the requirements of the API service MT-1 classification and is recommended by ExxonMobil for use in transmissions and gear cases where API Service GL-1 through GL-4 (non-EP) gear protection is required.

Features and Benefits

Mobil Delvac 1 Transmission Fluid 50 delivers exceptional performance in today's manual transmissions. The key benefits include:

Features	Advantages and Potential Benefits
Excellent load carrying, anti-wear, and EP performance	Extends transmission life and reduces cost of operation
Outstanding protection against deposit formation	Longer seal life, extended drain and service intervals
Maximum protection from corrosion of copper and its alloys	Protects and extends the life of synchronizers
Optimized thermal and oxidation protection	Extends component life and improves efficiency

Features	Advantages and Potential Benefits
Exceptional shear stability	Minimizes wear during severe operation
Outstanding low-temperature fluidity	Reduces wear during cold temperatures and improves shifting with quicker starts
Extended drain and service interval capability	Provides lower operating costs and higher productivity

Applications

Recommended by ExxonMobil for use in:

- Heavy-duty manual transmissions where extended service intervals and warranties are required
- Commercial line haul, vocational, off-road, pick-up and delivery, and bus applications
- Use as a companion with Mobil Delvac Synthetic Gear Oils in rear axles for maximum component life, service efficiency, and fuel economy improvement
- NOT suitable for hypoid gear applications in differentials and final drives, either for topping-off or refills, where API service GL-5, MIL-PRF-2105E or SAE J2360 lubricants are specified

Specifications and Approvals

Mobil Delvac 1 Transmission Fluid 50 meets or exceeds the requirements of the following industry and builder specifications:	
API MT-1	X

Mobil Delvac 1 Transmission Fluid 50 has the following builder approvals:	
Mack TO-A PLUS	X
Navistar MPAPS B-6816 Type 1	X
ZF FreedomLine	X

Mobil Delvac 1 Transmission Fluid 50 is recommended by ExxonMobil for use in applications requiring:	
Eaton PS-164 Rev 7	X

Typical Properties

Mobil Delvac 1 Transmission Fluid 50	
SAE Grade	50
Viscosity, ASTM D 445	
cSt @ 40°C	132
cSt @ 100°C	17.5
Viscosity Index, ASTM D 2270	146
Pour Point, °C, ASTM D 97	-45
Flash Point, °C, ASTM D 92	221
Density @ 15°C kg/l, ASTM D 4052	0.86

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design and Delvac are trademarks of Exxon Mobil Corporation, or one of its subsidiaries

04-2017

Exxon Mobil Corporation

22777 Springwoods Village Parkway
Spring TX 77389

1-800-ASK MOBIL (275-6624)

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

© Copyright 2003-2017 Exxon Mobil Corporation. All Rights Reserved.